

DXF-180D

FRONT-MOUNTED MULCHING ATTACHMENT

MADE FOR **MORE** TO KEEP PACE WITH **YOU!**

DENIS  **CIMAF**

Description	US	METRIC
Approx. Min Carrier Power	85 HP	65 kW
Cutting Width	74"	189 cm
Number of Teeth on Rotor	38 Dual-sided Carbide Teeth	
Target Material Diameter	8"	20 cm
Exterior Width	87"	221 cm
Height w/ Pushbar	56"	142 cm
Depth w/ Pushbar	53"	135 cm
Rotor Diameter	17"	43 cm
Optimal Rotor Speed	2,200 RPM	
Weight, with all options	2,950 lbs	1,339 kg
Hydraulic Motor Displacement	115 cc	
Max. Operating Pressure	5,000 psi	
Min Required Continuous Flow	35 gal/min	133 L

The Denis Cimaf DXF Mulching Head is a high-power, forestry brushcutting-mulching industrial system designed and built exclusively to mulch wood or vegetation residue on typical forest terrain and to reclaim untilled land.

The DXF mulching head is useful for:

- Shredding plants and branches in forests, of a diameter not exceeding the values indicated in the technical specifications for clearing undergrowth.
- To help maintain electric lines and funicular systems
- Mulching dead branches after forest clearance
- Creating Fire Lanes
- Shredding pruning residue
- Cultivation of new agricultural areas or grazing pastures
- Mulching organic waste for biomass use

The DXF mulching head features:

- Bolt-in wear liner
- Replaceable Skid Shoes
- Standard SAE attachment plate
- Start-up Kit

